

## CHANGING HD IN THE AMSTRAD DRX890


- 1: Remove the silver side panels by removing 2 screws on each panel then sliding the panels off: (pic1)
- 2: Remove the black case by lifting the black clips and sliding the main unit out: (pic2)
- 3: Remove the two cables from the front panel (they are quite stiff): (pic3)
- 4: Twist the 4 metal tabs on the top of the case (can be done with fingers to avoid leaving marks on the metal) and then lift the top panel off starting at the front of the box: (pic4)
- 5: Remove the front board by twisting 4 metal tabs and pushing 4 plastic ones back through the board: (pic5)
- 6: Remove all the screws and nuts from the metal panel there are lots of screws (keep them in order) I used a adjustable spanner to remove the nuts from the cable connectors: (pic6)
- 7: Use a knife or thin screwdriver to finish removing the back panel: (pic7)
- 8: Unplug the sata cable and the power cable from the HDD there are buttons on the underside of the cable connectors to release them correctly: (pic8)
- 9: Remove the screw and fan cable connector from the top board: (pic9)
- 10: Gently wiggle the top board upwards to free from connector shown in next picture: (pic10)
- 11: And the final steps are removing 5 screws holding the HDD in place: (pics 11&12)



Pic1



Pic2



Pic3





Pic4



Pic5



Pic6




Pic7





Pic8





Pic9



Pic10



**Pic11**



**Pic12**